

**SANYANG PETROLEUM**

55, Jalan SS25/32, Taman Mayang,
47301 Petaling Jaya, Selangor, Malaysia

Tel: +603-78031184 | Fax: +603-78031208

info@sanyangpetroleum.com

www.sanyangpetroleum.com

SANYANG HEAVY FUEL COMPONENT 80M

Heavy Aromatic Fuel Oil Component

SANYANG HEAVY FUEL COMPONENT 80M is a heavy oil with high content of aromatic compounds. The product may be applied as a component of high sulfur bunker oil HSFO 380 or HSFO 500 grades or as a component of other heavy fuel oils.

Parameter	Units	Min	Max	Test Methods
Density at 15°C	kg/m ³	990	1095	ASTM D 4052
Kinematic viscosity at 100°C	mm ² /s	20	55	ASTM D 445
Kinematic viscosity at 50°C	mm ² /s	380	3600	ASTM D 445
Pour point	°C	---	33	ASTM D 97
Flash point, COC	°C	100	---	ASTM D 92
Total sulfur content	wt.%	3.5	5.5	ASTM D 4294
Water content	v/v.%	---	0.1	ASTM D 95
Ash content	wt.%	---	0.03	ASTM D 482
Carbon residue micro	wt.%	---	4.99	ISO 10370

Guaranteed Storage Period: 6 months

Packing: ISO containers, tank trucks, vessels.

Marketed & Distributed by Sanyang Petroleum.