

**SANYANG PETROLEUM**

55 Jalan SS25/32, Taman Mayang
47301 Petaling Jaya, Selangor, Malaysia
Tel: +603-78031184 | Fax: +603-78031208
info@sanyangpetroleum.com
www.sanyangpetroleum.com

PRODUCT SPECIFICATION

Product Name:	Industry White Oil 68#
Date of Production:	2026/4/7

Item	Unit	Specification	Typical Value	Method
Appearance	-	Colorless, odorless, non-fluorescent, transparent liquid	Colorless, odorless, non-fluorescent, transparent liquid	Visual observation
Kinematics Viscosity at 40°C	mm ² /s	61.2-74.8	64.54	ASTM D445 / GB/T 265-1988(2004)
Kinematics Viscosity at 100°C	mm ² /s	report	8.963	ASTM D445 / GB/T 265
Viscosity Index	mm ² /s	report	114	ASTM D2270 / GB/T 1995
Flash Point-Open cup	°C	≥200	264	ASTM D92 / GB/T 3536-2008
Pour Point	°C	≤ -9	-13	ASTM D97 / GB/T 3535-2006
Saybolt color	-	≥ +23	+30	ASTM D156 / GB/T 3555-2022
Copper Strip Corrosion(100°C,3h)	class	≤1	1	ASTM D130 / GB/T 5096-2017
Sulfur	mg/Kg	≤7	2.0	ASTM 5453 / SH/T 0689-2000
Aromatic Hydrocarbon	mg(KOH)/g	≤3.5	2.0	ASTM D1319 / NB/SH/T 0966-2017
Water	-	None	None	ASTM D95 / GB/T 260
Mechanical Impurity	-	None	None	ASTM D473 / GB/T511
Water-soluble Acids and Alkalis	-	None	None	ASTM D130 / GB/T 259

Marketed & Distributed by Sanyang Petroleum.